



HURRICANE


CONCRETE BREAKER HIGH PRODUCTION DESTRUCTION

Simple to operate, minimal operator training

Compact design, easy hook-up

Low maintenance, low cost breaking

Fits to skidsteers, excavators and backhoes



ROCKTEC
Rock Technology



HURRICANE

CONCRETE BREAKER

► Features

The Rocktec Hurricane has been designed to provide high impact concrete breaking whilst ensuring that both the carrier and operator are shielded from the impact forces.

Standard features include:

- heavy duty construction
- Simple hydraulic hook up
- Skid system that effectively grounds the impact.
- No grease nipples or accumulators
- Simple mounting to skidsteers, mini skidsteers and excavators.
- 3 sizes available
- High impact "cleans" concrete off reinforcing
- Top of concrete remains smooth whilst underneath is shattered through the full concrete thickness.

► Noise

Due to the high impact and low blow frequency the accumulative noise of the Hurricane is much lower than that of a conventional hydraulic hammer. This has the effect of lowering the "annoyance" factor for operators and bystanders.



► Technical Specifications

Rocktec Hurricanes are built to the same exacting specifications to ensure every machine gives the same long life reliability that is standard on Rocktec equipment.

Standard specifications include:

Hydraulics

- Purpose built valve block
- Pre set hydraulic elements
- Internal over pressure relief
- Flow control

Drive Assembly

- Sealed, long life bearings
- High quality motor
- Simple chain adjustment
- Hardened sprockets
- Extra long life chain

Body

- Heavy duty, computer aided design
- Hardened ground engaging skids
- Full length chain support

Hammer

- Super long life
- One piece design
- No replacement parts



- Simple to operate
- Minimal operator training
- Compact design
- Easy hook up
- Low maintenance
- Low cost breaking
- Fits to skidsteers, excavators and backhoes



HURRICANE

CONCRETE BREAKER

Specifications		Force 7	Force 9	Force 10
Impact Energy	Nm	1125 / 1500	2720 / 4490	8700 / 11500
Blows per minute	adjustable	30 - 40	30 - 40	25 - 30
Operating weight	kg	320	720	1425
Oil flow demand	lpm	20 - 35	30 - 50	60 - 100
Hydraulic pressure - minimum	bar	150	150	150
Hydraulic pressure - maximum	bar	200	200	200
Operating height	m	2.1	2.3	2.7
Height x width x depth		1.5 x 0.4 x 0.4	1.5 x 0.5 x 0.5	1.8 x 0.7 x 0.7



11 Waihou Street | Private Bag 4072 | Matamata 3440 | New Zealand
 phone +64 7 881 9188 or 0800 735 305 | fax + 64 7 888 6856
 email sales@rocktec.co.nz | website www.rocktec.co.nz

ROCKTEC
 Rock Technology